

Wall terminals · Z-Wave

Space Pad Classic Keypad

Z-Wave keypad with a potential-free contact for electric strikes and gate operators.

Model: **Space Pad**



Overview

The Space Pad keypad is a Z-Wave device powered by 9 to 36 V DC. Its built-in potential-free contact makes it ideal for use with electric strikes.

The keypad can also trigger most popular entrance gate operators.

Key functions

PIN code

Unlocking with a PIN code.

MIFARE card

Unlocking with a MIFARE 1K card.

Mobile app

Unlocking via the mobile app.

NO / COM / NC contact

A potential-free contact for electric strikes and gate operators.

IP55


Ingress protection IP55; operation from -20 to +70 °C.

Users

221 standard users and 9 administrators.

Specifications

Product	Space Pad
Communication	Z-Wave 800, 868.42 MHz (EU)
Unlocking	Card, app, code
Card type	MIFARE 1K
Power supply	9–36 V DC
Standby current	65 μ A
Potential-free contact	NO, COM, NC
Ingress protection	IP55
Standard users	221
Administrators	9
Operating temperature	–20...+70 °C
Operating humidity	10–95%
Material	PET
Colour	Black
Mounting	Surface-mounted
Optional, on order	Bluetooth 6.0 (BLE) module: automatic opening with a BLE beacon and direct local connection to the app



Dimensions in mm.

Works with the SPACE system

Z-Wave 800 communication. Unlocking via PIN code, MIFARE card or the mobile app.

Ordering

- Available in the SPACE online shop: portal.spacebms.com.
- For larger projects we prepare an individual quote.
- Installation and commissioning by SPACE or an authorised installer.

Contact and orders

+48 533 909 533

support@spacebms.com · www.spacebms.com

Space BMS sp. z o.o., ul. Zbożowa 3/6, 30-002 Kraków